

IS: 3957 - 1966

(Reaffirmed 1983)

Indian Standard QUALITY TOLERANCES FOR WATER FOR ICE MANUFACTURE

(Third Reprint MARCH 1989)

UDC 663.61:621.58

© Copyright 1967

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard QUALITY TOLERANCES FOR WATER FOR ICE MANUFACTURE

Water Sectional Committee, CDC 26

Chairman

Representing

DR T. R. BHASKARAN

Indian Council of Medical Research, New Delhi

Members

SHRI K. L. BANERJEE

National Test House, Calcutta

SHRI N. C. SENGUPTA (Alternate)

DR P. R. BAVDEKAR

Tata Chemicals Ltd, Bombay

DR R. P. DAROGA (Alternate) SHRI M. V. BOPARDIKAR

Central Public Health Engineering Research Institute (CSIR), Nagpur

CHEMIST & METALLURGIST,

Railway Board (Ministry of Railways)

CENTRAL RAILWAY, BOMBAY SECTIONAL OFFICER (CM).

CHITTARANJAN (Alternate)
DR I. G. Dos M. Pais Cuddou.

SHRI N. C. RAWAL (Alternate)

Central Water & Power Commission, New Delhi

SHRI R. R. DEO

The Paterson Engineering Co (India) Private Ltd, Calcutta

Dr.N. F. DESAI DIRECTOR OF SCIENTIFIC RE-

Sandoz (India) Ltd, Bombay Naval Headquarters

SEARCH (NAVY)

Scientific Officer (ICE) (Alternate)

DR M. I. GURBAXANI

DR B. B. PAUL SHRI N. N. MEHTA (Alternate)

DR S. C. PILLAI

SHRI C. V. S. RATNAM

SHRI G. M. RAWAL

The Tata Iron & Steel Co Ltd, Jamshedpur All India Distillers' Association, New Delhi

Indian Institute of Science, Bangalore Neyveli Lignite Corporation Ltd, Neyveli The Tata Hydro-Electric Power Supply Co Ltd,

Bombay

SHRI R. K. BASU (Alternate)

DR V. SADASIVAN DR B. SARMA

Bombay Municipal Corporation, Bombay

SHRI V. K. RAIZADA (Alternate) SHRI B. A. SHOLAPURWALA

SHRI V. M. SHAH (Alternate)

SHRI B. C. SHOME

DR R. MOUDGAL (Alternate) SHRI K. G. VEERARAGHAVAN

Ministry of Defence (R & D)

Italab Private Ltd, Bombay

ICI (India.) Private Ltd, Calcutta

Director of Public Health, Government of Madras

(Continued on page 2)

TContinued from page 1)

Members

DR K. VENKATARAMANAN

SHRI M. R. VERMA DR SADGOPAL, Director (Chem) Representing

Directorate General of Health Services (Ministry of Health) National Physical Laboratory (CSIR), New Delhi

Director General, ISI (Ex-officio Member)

Secretary

DR G. M. SAXENA

Deputy Director (Chem), ISI

Water For Industrial Purposes Subcommittee, CDC 26:2

Convener

SHRI R. R. DEO

The Paterson Engineering Co (India) Pvt Ltd, Calcutta

Members

SHRI K. R. BULUSU

SHRI S. D. DANDEKAR DR N. F. DESAI SHRI E. K. JAYANARAYANAN DR V. SADASIVAN SHRI S. SAMPATH

SHRI N. V. PARTHASARADHY (Alternate)
SHRI B. A. SHOLAPURWALA
SHRI V. M. SHAH (Alternate)
SHRI M. R. SRINIVASAN
SHRI M. G. VEERARAGHAVAN
Director of

Central Public Health Engineering Research Institute (CSIR), Nagpur Camlin Private Ltd, Bombay Sandoz (India) Ltd, Bombay Dyer Meakin Breweries Ltd, Solan Bombay Municipal Corporation, Bombay Central Electrochemical Research Institute (CSIR) Karaikudi

Alternate) Italab Private Ltd, Bombay

National Dairy Research Institute, Karnal Director of Public Health, Government of Madras

Indian Standard QUALITY TOLERANCES FOR WATER FOR ICE MANUFACTURE

O. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 24 September 1966, after the draft finalized by the Water Sectional Committee had been approved by the Chemical Division Council.

0.2 Ice is manufactured in a number of food industries, in cold storage plants and exclusively in ice-making industry. Good quality ice should be clear, colourless, free from air bubbles, snowy butts and heavy cores. It should not shatter when handled. On melting, it should give a water of potable quality in its bacteriological, physical and chemical features. Hence the quality of water used in ice making is of utmost public health importance.

0.3 In preparing this standard, assistance has been obtained from the following publications:

United States of America. California State Water Pollution Control Board. Mckee and Wolf. Water quality criteria. Ed 2 (Publication No. 3A). 1963. Sacramento.

Special Technical Publication 148-D. 1959. Manual on industrial water. Ed 2. American Society for Testing and Materials, USA.

0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the quality tolerances for water used in ice manufacture.

2. TOLERANCES

2.1 The water shall comply with the tolerances given in Tables 1 to 3 for its bacteriological; physical and chemical; and radioactive characteristics when tested according to the methods given in IS: 1622-1964† and

^{*}Rules for rounding off numerical values (revised).

[†]Methods of sampling and test for microbiological examination of water used in industry.

IS: 3025-1964*. Reference to the relevant clauses of these standards is given in col 4 of Table 1, Table 2 and Table 3.

678 A 578 F 578 A			40. D = 4 = Wester
A / LA / LA / L	T. O. 10	BACTERIOLOGICAL	· · · · · · · · · · · · · · · · · · ·

(Clause 2.1)

SL No.	CHARACTERISTIC	Tolerance	METHOD of TEST (REF TO CL No. IN IS: 1622- 1964*)
(1)	(2)	(3)	(4)
i) (Coliform bacteria, MPN index per 100 ml, Max	Less than 1	3.2
ii) S	Standard plate count, per ml, Max	100	5
* 1/4	ethode of sampling and test for microbiological	evemination	of water need in

^{*}Methods of sampling and test for microbiological examination of water used in industry.

TABLE 2 TOLERANCES FOR PHYSICAL AND CHEMICAL QUALITY (Clause 2.1)

St No.	Characteristic	Tolerance	METHOD OF TEST (REF TO CA NO. IN IS: 3025- 1964*)
(1)	(2)	(3)	(4)
i)	Colour (Hazen units), Max	5	5
ii)	Turbidity, units, Max	5	
iii)	Odour	None	6 7
iv)	ρH	6.5 to 9.2	. 8
v)	Total dissolved solids, mg/1, Max	1 000+	12
vi)	Alkalinity (as CaCO ₂), mg/1, Max	100	13
vii)	Total hardness (as CaCO ₈), mg/1, Max	600	16
viii)	Sulphate (as SO ₄), mg/1, Max	200	20
ix)	Fluoride (as F), mg/l, Max	1.5	23
x)	Chloride (as Cl), mg/l, Max	250	24
xi)	Cyanide (as CN), mg/1, Max	0.01	27
xii)	Selenium (as Se), mg/1, Max	0.05	28
xiii)	Iron (as Fe), mg/1, Max	0.3	32
xiv)	Magnesium (as Mg), mg/1, Max	125	34
xv)	Manganese (as Mn), mg/l, Max	0.2	35
xvi)		1.0	36
xvii)	Lead (as Pb), mg/1, Max	0.1	37
xviii)	Chromium (as Cr ^{s+}), mg/1, Max	0.05	38
xix)	Zinc (as Zn), mg/1, Max	15:0	39
xx)	Arsenic (as As), mg/1, Max	0.2	40
xxi)	Phenolic substances (as C ₆ H ₈ OH), mg/1, Max	0.001	54
	nods of sampling and test (physical and chemical clear, transparent ice, total dissolved solid content	1	
1 ror c	ical, transparent ice, total dissolved solid content	snould not exc	cea and mg/1.

^{*}Methods of sampling and test (physical and chemical) for water used in industry.

TABLE 3 TOLERANCES FOR RADIOACTIVITY

(Clause 2.1)

SL No.	Ch araoteristic	TOLEBANCE	METHOD OF TEST (REF TO CL No. IN IS:3025-1964*)	
(1)	(2)	(3)	(4)	
i)	Alpha emitters, μ c/ml, Max	10-• ๅ		
ii)	Beta emitters, µ c/ml, Max	10-• }	58	
• Metho	ods of sampling and test (physical and c	hemical) for water	used in industry.	

3. SAMPLING

3.1 Representative test samples of water shall be drawn as prescribed in 2 of IS: 1622-1964* and 2 of IS: 3025-1964*.

4. TEST METHODS

4.1 Tests shall be carried out as prescribed in the appropriate clauses, indicated against the characteristic in Table 1, Table 2 and Table 3, of IS: 1622-1964* and IS: 3025-1964*.

^{*}Methods of sampling and test for microbiological examination of water used in industry.

[†]Methods of sampling and test (physical and chemical) for water used in industry.

